## NSN 5305-01-030-1078

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-030-1078 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.391 inches **Fastener Length:** Between 1.886 inches and 1.906 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.752 inches and 0.762 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 1.490 inches and 1.510 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 14000 pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp 4140 or steel comp 8740 **Material Specification:** Mil-s-55626 military specification single material response or mil-s-6046 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1156 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5305-01-030-1078

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-55626 spec.