## NSN 5305-01-030-8753

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-030-8753 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.218 inches and 0.310 inches **Fastener Length:** Between 0.280 inches and 0.310 inches **Head Style:** Hexagon **Head Height:** Between 0.080 inches and 0.093 inches Width Between Flats: Between 0.244 inches and 0.250 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 60000 pounds per square inch **Screw Material:** Steel **Screw Material Specification:** Qq-s-637 federal specification 1st material response or federal standard 66 federal standard 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification 1st treatment response or mil-c-81562 type 2 cl 3 military specification 2nd treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 1 type and 10s style Shelf Life: N/a **Unit Of Measure:** 

No

Fiig:

A500d0

**Demilitarization:** 

## NSN 5305-01-030-8753

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-81562 spec.