NSN 5305-01-030-9120

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-030-9120

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.412 inches and 0.452 inches |
| Fastener Length: |
| Between 0.490 inches and 0.510 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.121 inches and 0.133 inches |
| Width Between Flats: |
| Between 0.243 inches and 0.251 inches |
| Hole Diameter: |
| 0.047 inches |
| Thread Diameter: |
| 0.138 inches |
| Hole Quantity: |
| 1 |
| Thready Qty Per Inch (tpi): |
| 40 |
| Min. Tensile Strength (psi): |
| 130000 pounds per square inch |
| Hardness Rating: |
| Between 24.0 rockwell c and 35.0 rockwell c |
| Screw Material: |
| Iron alloy 660 |
| Screw Material Specification: |
| Ams 5731 assn standard single material response |
| Head Hole Configuration Style: |
| Hexagon flats |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| |