## NSN 5305-01-031-0756

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-031-0756

| view Offilitie at https://aerobasegroup.com/nsi//0505-01-051-0750                 |
|---|
| Thread Class:   |
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| Between 0.387 inches and 0.500 inches   |
| Fastener Length:  |
| Between 0.470 inches and 0.500 inches   |
| Head Style:   |
| Flat chamfer  |
| Head Diameter:  |
| Between 0.550 inches and 0.562 inches   |
| Head Height:  |
| Between 0.368 inches and 0.375 inches   |
| Locking Feature:  |
| Patch threads or pellet threads or strip threads                                  |
| Internal Drive Style:   |
| Hexagon   |
| Thread Diameter:  |
| 0.375 inches  |
| Width Across Flats:   |
| Between 0.312 inches and 0.316 inches   |
| Thready Qty Per Inch (tpi):   |
| 24  |
| Min. Tensile Strength (psi):  |
| 170000 pounds per square inch   |
| Hardness Rating:  |
| 38.0 rockwell c and 45.0 rockwell c   |
| Minimum Yield Strength:   |
| 150000 pounds per square inch   |
| Material:   |
| Steel fastener  |
| Surface Treatment:  |
| Cadmium fastener and chromate fastener  |
| Surface Treatment Specification:  |
| Qq-p-416, type 2 class 2 federal specification single treatment response fastener |
| Thread Series Designator:   |
| Unrf  |
| Specification Data:   |
| 80205-nas1351 professional/industrial association standard                        |
| Shelf Life:   |
| N/a   |

## NSN 5305-01-031-0756

Socket Head Cap Screw - Page 2 of 2



|  |  |  | ure: |  |
|--|--|--|------|--|
|  |  |  |      |  |
|  |  |  |      |  |

--

Demilitarization:

No

Fiig:

A003b0