NSN 5305-01-031-3212

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-031-3212

Thread Direction: Right-hand Thread Length: 0.125 inches Fastener Length: 0.562 inches Head Style: Round extended washer Head Diameter: Between 0.365 inches and 0.385 inches Head Height: Between 0.089 inches and 0.099 inches Extended Washer Diameter: Between 0.427 inches and 0.447 inches Extended Washer Thickness: Between 0.025 inches and 0.030 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi):
Right-hand Thread Length: 0.125 inches Fastener Length: 0.562 inches Head Style: Round extended washer Head Diameter: Between 0.365 inches and 0.385 inches Head Height: Between 0.089 inches and 0.099 inches Extended Washer Diameter: Between 0.427 inches and 0.447 inches Extended Washer Thickness: Between 0.025 inches and 0.030 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32
Thread Length: 0.125 inches Fastener Length: 0.562 inches Head Style: Round extended washer Head Diameter: Between 0.365 inches and 0.385 inches Head Height: Between 0.089 inches and 0.099 inches Extended Washer Diameter: Between 0.427 inches and 0.447 inches Extended Washer Thickness: Between 0.025 inches and 0.030 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32
0.125 inches Fastener Length: 0.562 inches Head Style: Round extended washer Head Diameter: Between 0.365 inches and 0.385 inches Head Height: Between 0.089 inches and 0.099 inches Extended Washer Diameter: Between 0.427 inches and 0.447 inches Extended Washer Thickness: Between 0.025 inches and 0.030 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32
Fastener Length: 0.562 inches Head Style: Round extended washer Head Diameter: Between 0.365 inches and 0.385 inches Head Height: Between 0.089 inches and 0.099 inches Extended Washer Diameter: Between 0.427 inches and 0.447 inches Extended Washer Thickness: Between 0.025 inches and 0.030 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32
O.562 inches Head Style: Round extended washer Head Diameter: Between 0.365 inches and 0.385 inches Head Height: Between 0.089 inches and 0.099 inches Extended Washer Diameter: Between 0.427 inches and 0.447 inches Extended Washer Thickness: Between 0.025 inches and 0.030 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32
Head Style: Round extended washer Head Diameter: Between 0.365 inches and 0.385 inches Head Height: Between 0.089 inches and 0.099 inches Extended Washer Diameter: Between 0.427 inches and 0.447 inches Extended Washer Thickness: Between 0.025 inches and 0.030 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32
Round extended washer Head Diameter: Between 0.365 inches and 0.385 inches Head Height: Between 0.089 inches and 0.099 inches Extended Washer Diameter: Between 0.427 inches and 0.447 inches Extended Washer Thickness: Between 0.025 inches and 0.030 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32
Head Diameter: Between 0.365 inches and 0.385 inches Head Height: Between 0.089 inches and 0.099 inches Extended Washer Diameter: Between 0.427 inches and 0.447 inches Extended Washer Thickness: Between 0.025 inches and 0.030 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32
Between 0.365 inches and 0.385 inches Head Height: Between 0.089 inches and 0.099 inches Extended Washer Diameter: Between 0.427 inches and 0.447 inches Extended Washer Thickness: Between 0.025 inches and 0.030 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32
Head Height: Between 0.089 inches and 0.099 inches Extended Washer Diameter: Between 0.427 inches and 0.447 inches Extended Washer Thickness: Between 0.025 inches and 0.030 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32
Between 0.089 inches and 0.099 inches Extended Washer Diameter: Between 0.427 inches and 0.447 inches Extended Washer Thickness: Between 0.025 inches and 0.030 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32
Extended Washer Diameter: Between 0.427 inches and 0.447 inches Extended Washer Thickness: Between 0.025 inches and 0.030 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32
Between 0.427 inches and 0.447 inches Extended Washer Thickness: Between 0.025 inches and 0.030 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32
Extended Washer Thickness: Between 0.025 inches and 0.030 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32
Between 0.025 inches and 0.030 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32
Internal Drive Style: Cross recess type 1 Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32
Cross recess type 1 Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32
Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32
0.190 inches Thready Qty Per Inch (tpi): 32
Thready Qty Per Inch (tpi): 32
32
-
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
Between 26.0 rockwell c and 32.0 rockwell c
Screw Material:
Steel
Screw Material Specification:
Qq-s-698 federal specification single material response
Screw Surface Treatment:
Cadmium
Screw Surface Treatment Specification:
An-p-61 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5305-01-031-3212

Machine Screw - Page 2 of 2



em			

No

Fiig:

A500d0