

View Online at <https://aerobasegroup.com/nsn/5305-01-031-4355>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.277 inches

Fastener Length:

Between 0.637 inches and 0.667 inches

Head Style:

Watertight

Head Diameter:

Between 0.360 inches and 0.370 inches

Head Height:

Between 0.095 inches and 0.100 inches

Locking Feature:

Strip threads

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Special Features:

Furnished with one plastic /polytetrafluoroethylene/shim and one synthetic rubber /silicone/ o-ring

Material:

Steel comp 304l or steel comp 316l or steel comp 302 or steel comp 303 or steel comp 347 or steel comp 321 or steel comp 317 or steel comp 316 or steel comp 310 or steel comp 309 or steel comp 305 or steel comp 304 or steel comp 303se

Surface Treatment:

Passivate or oxide

Surface Treatment Specification:

Qq-p-35 federal specification 1st treatment response or mil-c-13924, cl 1 military specification 2nd treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.