

View Online at <https://aerobasegroup.com/nsn/5305-01-031-5084>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.187 inches and 0.207 inches

Fastener Length:

Between 0.407 inches and 0.437 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.195 inches and 0.225 inches

First Diameter From Head:

Between 0.070 inches and 0.074 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.250 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Countersink Angle:

81.0 degrees

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 304l or steel comp 316l or steel comp 302 or steel comp 347 or steel comp 321 or steel comp 317 or steel comp 316 or steel comp 310 or steel comp 309 or steel comp 305 or steel comp 304 or steel comp 301 or steel comp 303 or steel comp 303f or steel comp 303se or steel comp 308 or steel comp 309s or steel comp 310s or steel comp 314 or steel comp 323 or steel comp 324 or steel comp 348 or steel comp 385

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0