NSN 5305-01-031-5084



Externally Relieved Body Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-031-5084 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.187 inches and 0.207 inches **Fastener Length:** Between 0.407 inches and 0.437 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.195 inches and 0.225 inches **First Diameter From Head:** Between 0.070 inches and 0.074 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.250 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Countersink Angle:** 81.0 degrees **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 304l or steel comp 316l or steel comp 302 or steel comp 347 or steel comp 321 or steel comp 317 or steel comp 316l o comp 310 or steel comp 309 or steel comp 305 or steel comp 304 or steel comp 301 or steel comp 303 or steel comp 303 or steel comp 303se or steel comp 308 or steel comp 309s or steel comp 310s or steel comp 314 or steel comp 323 or steel comp 324 or steel comp 348 or steel comp 385 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Fiig:

No

Demilitarization: