

View Online at <https://aerobasegroup.com/nsn/5305-01-031-5090>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.344 inches and 0.406 inches

**Fastener Length:**

Between 1.594 inches and 1.656 inches

**Head Style:**

Round extended washer

**Head Diameter:**

0.375 inches

**Head Height:**

Between 0.089 inches and 0.099 inches

**Extended Washer Diameter:**

0.437 inches

**Extended Washer Thickness:**

Between 0.025 inches and 0.030 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Screw Material:**

Steel comp 4037 or steel comp 8630

**Screw Material Specification:**

Ams6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response

**Screw Surface Treatment:**

Cadmium and chromate

**Screw Surface Treatment Specification:**

Qq-p-416, type 2 cl 3 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0

**Mil-std (military Standard):**

Mil-s-6050 spec.