Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-031-8418

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.750 inches
Fastener Length:
1.125 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.457 inches and 0.469 inches
Head Height:
Between 0.306 inches and 0.312 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.312 inches
Width Across Flats:
0.250 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
165000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 42.0 rockwell c
Minimum Yield Strength:
155000 pounds per square inch
Criticality Code Justification:
Zzzw
Material:
Steel
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Thread Series Designator:
Unf
Departure From Cited Document:
As differentiated by special quality control testing for mk 48 torpedo
Shelf Life:
N/a

## NSN 5305-01-031-8418

Socket Head Cap Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

