
NSN 5305-01-031-8446

Socket Head Cap Screw - Page 1 of 2





Thread	l Class:
3a	
Thread	I Direction:
Right-h	and
Thread	I Length:
Betwee	en 0.657 inches and 0.750 inches
Fasten	er Length:
Betwee	en 0.719 inches and 0.750 inches
Head S	Style:
Flat cha	amfer
Head [Diameter:
Betwee	en 0.221 inches and 0.226 inches
Head H	leight:
Betwee	en 0.134 inches and 0.138 inches
Lockin	g Feature:
Strip th	reads
Interna	Il Drive Style:
Hexago	on la constante de la constante
Thread	I Diameter:
0.138 i	nches
Width	Across Flats:
0.095 i	nches
Thread	ly Qty Per Inch (tpi):
32	
Color:	
Black fa	astener
Materia	al:
Steel c	omp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 384 fastener or
steel co	omp xm-7 fastener
Surfac	e Treatment:
Oxide f	astener
Surfac	e Treatment Specification:
Mil-c-1	3924 cl 2 military specification single treatment response fastener
Thread	Series Designator:
Unc	
Shelf L	.ife:
N/a	
Unit Of	Measure:
Demili	tarization:
No	
Fiig:	
A003b0	

NSN 5305-01-031-8446

Socket Head Cap Screw - Page 2 of 2

Mil-std (military Standard):

Mil-c-13924 spec.

