

View Online at <https://aerobasegroup.com/nsn/5305-01-032-3432>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.294 inches and 0.325 inches

**Fastener Length:**

Between 0.344 inches and 0.375 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.205 inches and 0.218 inches

**Head Height:**

Between 0.070 inches and 0.080 inches

**Locking Feature:**

Pellet threads

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Material:**

Steel comp 304l or steel comp 316l or steel comp 302 or steel comp 347 or steel comp 321 or steel comp 317 or steel comp 316 or steel comp 310 or steel comp 309 or steel comp 305 or steel comp 304

**Material Specification:**

Qq-s-763 and federal standard 66 federal specification all material responses

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0