

View Online at <https://aerobasegroup.com/nsn/5305-01-032-8271>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.168 inches and 0.250 inches

**Fastener Length:**

Between 0.218 inches and 0.250 inches

**Head Style:**

Pan no. 2

**Head Diameter:**

Between 0.205 inches and 0.219 inches

**Head Height:**

Between 0.058 inches and 0.068 inches

**Washer Quantity:**

2

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

55000 pounds per square inch

**Secondary Washer Relationship To Primary Washer:**

Not identical

**Secondary Washer Style:**

Flat

**Primary Washer Outside Diameter:**

0.209 inches

**Secondary Washer Outside Diameter:**

Between 0.213 inches and 0.223 inches

**Primary Washer Style:**

Split helical ring

**Primary Washer Material Thickness:**

0.025 inches

**Secondary Washer Material Thickness:**

Between 0.013 inches and 0.019 inches

**Material:**

Copper alloy 510 secondary washer

**Material Specification:**

Qq-b-750 federal specification single material response secondary washer

**Surface Treatment:**

Tin

**Thread Series Designator:**

Unc

**Specification Data:**

80205-nas 720 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0