# NSN 5305-01-032-8575

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-032-8575



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 0.527 inches and 0.620 inches

#### Fastener Length:

Between 0.657 inches and 0.688 inches

#### **Head Style:**

Flat countersunk

#### Head Diameter:

Between 0.282 inches and 0.332 inches

#### Internal Drive Style:

Cross recess type 1

### Thread Diameter:

0.164 inches

#### Thready Qty Per Inch (tpi):

32

### Min. Tensile Strength (psi):

125000 pounds per square inch

#### Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

#### Countersink Angle:

100.0 degrees

#### Screw Material:

Steel comp 4037 or steel comp 8630

#### Screw Material Specification:

Ams 6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response

#### Screw Surface Treatment:

Cadmium and chromate

#### Screw Surface Treatment Specification:

Qq-p-416, type 2 cl 2 federal specification single treatment response

#### **Thread Series Designator:**

Unjc

# **Specification Data:**

80205-nas514 professional/industrial association standard

## Shelf Life:

N/a

# Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5305-01-032-8575

Machine Screw - Page 2 of 2

**Fiig:** A500d0

Mil-std (military Standard):

Mil-s-6050 spec.

