

View Online at <https://aerobasegroup.com/nsn/5305-01-033-2661>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.293 inches and 0.375 inches

**Fastener Length:**

Between 0.914 inches and 0.940 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.357 inches and 0.375 inches

**Head Height:**

Between 0.182 inches and 0.188 inches

**Shoulder Diameter:**

0.247 inches first shoulder and 0.248 inches first shoulder

**Shoulder Length:**

0.559 inches first shoulder and 0.565 inches first shoulder

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.190 inches

**Width Across Flats:**

0.125 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 43.0 rockwell c

**Shoulder Shape:**

Round first shoulder

**Product Name:**

Navy special project

**Special Features:**

Strip type locking element on threads

**Material:**

Steel

**Surface Treatment:**

Cadmium and chromate or cadmium

**Surface Treatment Specification:**

Qq-p-416 type 2 federal specification 1st treatment response or p-4 fscm 56878 federal specification 2nd treatment response

**Thread Series Designator:**

Unrf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0