NSN 5305-01-034-2828

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-034-2828

The Common at the part and according to the control of the control
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.720 inches and 0.750 inches
Fastener Length:
Between 4.475 inches and 4.495 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.853 inches and 0.875 inches
Head Height:
Between 0.365 inches and 0.375 inches
Shoulder Diameter:
0.621 inches first shoulder and 0.623 inches first shoulder
Shoulder Length:
3.745 inches first shoulder and 3.755 inches first shoulder
Single Shear Strength:
10400 pounds per square inch
Internal Drive Style:
Hexagon
Thread Diameter:
0.500 inches
Width Across Flats:
0.312 inches
Thready Qty Per Inch (tpi):
13
Min. Tensile Strength (psi):
140000 pounds per square inch
Hardness Rating:
32.0 rockwell c and 43.0 rockwell c
Shoulder Shape:
Round first shoulder
Material:
Steel
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, ty2 cl 3 federal specification single treatment response
Thread Series Designator:
Unc

Unc

NSN 5305-01-034-2828

Shoulder Screw - Page 2 of 2



_					
CI	~~	14	I i	ife:	
J.	16			HE.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0