NSN 5305-01-034-2828

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-034-2828

The Common at the part and according to the control of the control					
Thread Class:					
3a					
Thread Direction:					
Right-hand					
Thread Length:					
Between 0.720 inches and 0.750 inches					
Fastener Length:					
Between 4.475 inches and 4.495 inches					
Head Style:					
Flat chamfer					
Head Diameter:					
Between 0.853 inches and 0.875 inches					
Head Height:					
Between 0.365 inches and 0.375 inches					
Shoulder Diameter:					
0.621 inches first shoulder and 0.623 inches first shoulder					
Shoulder Length:					
3.745 inches first shoulder and 3.755 inches first shoulder					
Single Shear Strength:					
10400 pounds per square inch					
Internal Drive Style:					
Hexagon					
Thread Diameter:					
0.500 inches					
Width Across Flats:					
0.312 inches					
Thready Qty Per Inch (tpi):					
13					
Min. Tensile Strength (psi):					
140000 pounds per square inch					
Hardness Rating:					
32.0 rockwell c and 43.0 rockwell c					
Shoulder Shape:					
Round first shoulder					
Material:					
Steel					
Surface Treatment:					
Cadmium and chromate					
Surface Treatment Specification:					
Qq-p-416, ty2 cl 3 federal specification single treatment response					
Thread Series Designator:					
Unc					

Unc

NSN 5305-01-034-2828

Shoulder Screw - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0