

View Online at <https://aerobasegroup.com/nsn/5305-01-034-2828>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.720 inches and 0.750 inches

**Fastener Length:**

Between 4.475 inches and 4.495 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.853 inches and 0.875 inches

**Head Height:**

Between 0.365 inches and 0.375 inches

**Shoulder Diameter:**

0.621 inches first shoulder and 0.623 inches first shoulder

**Shoulder Length:**

3.745 inches first shoulder and 3.755 inches first shoulder

**Single Shear Strength:**

10400 pounds per square inch

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.500 inches

**Width Across Flats:**

0.312 inches

**Thready Qty Per Inch (tpi):**

13

**Min. Tensile Strength (psi):**

140000 pounds per square inch

**Hardness Rating:**

32.0 rockwell c and 43.0 rockwell c

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, ty2 cl 3 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0