Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-035-2284

Thread Class: 2a Thread Direction: Right-hand Thread Length: 0.188 inches Fastener Length: Between 0.408 inches and 0.438 inches Head Style: Pan Head Diameter: Between 0.256 inches and 0.270 inches Head Height: Between 0.256 inches and 0.270 inches First Diameter From Head: Between 0.087 inches and 0.097 inches First Diameter From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Internal Drive Style: Stot Thread Diameter: 0.138 inches
Thread Direction: Right-hand Thread Length: 0.188 inches Fastener Length: Between 0.408 inches and 0.438 inches Head Style: Pan Head Diameter: Between 0.256 inches and 0.270 inches Head Height: Between 0.087 inches and 0.097 inches First Diameter From Head: Between 0.087 inches and 0.099 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Distance From Largest Bearing Surface Of Head To End Of First Diameter: Distance From Largest Bearing Surface Of Head To End Of First Diameter: Distance From Largest Bearing Surface Of Head To End Of First Diameter: Distance From Largest Bearing Surface Of Head To End Of First Diameter: Distance From Largest Bearing Surface Of Head To End Of First Diameter: Distance From Largest Bearing Surface Of Head To End Of First Diameter: Distance From Largest Bearing Surface Of Head To End Of First Diameter: Distance From Largest Bearing Surface Of Head To End Of First Diameter: Distance From Largest Bearing Surface Of Head To End Of First Diameter: Distance From Largest Bearing Surface Of Head To End Of First Diameter: Distance From Largest Bearing Surface Of Head To End Of First Diameter: Distance From Largest Bearing Surface Of Head To End Of First Diameter: Dis
Right-hand Thread Length: O.188 inches Fastener Length: Between 0.408 inches and 0.438 inches Head Style: Pan Head Diameter: Between 0.256 inches and 0.270 inches Head Height: Between 0.087 inches and 0.097 inches First Diameter From Head: Between 0.087 inches and 0.099 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Internal Drive Style: Slot Thread Diameter: O.138 inches
Thread Length: 0.188 inches Fastener Length: Between 0.408 inches and 0.438 inches Head Style: Pan Head Diameter: Between 0.256 inches and 0.270 inches Head Height: Between 0.087 inches and 0.097 inches First Diameter From Head: Between 0.087 inches and 0.099 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Internal Drive Style: Slot Thread Diameter: 0.138 inches
0.188 inches Fastener Length: Between 0.408 inches and 0.438 inches Head Style: Pan Head Diameter: Between 0.256 inches and 0.270 inches Head Height: Between 0.087 inches and 0.097 inches First Diameter From Head: Between 0.087 inches and 0.099 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Internal Drive Style: Slot Thread Diameter:
Fastener Length: Between 0.408 inches and 0.438 inches Head Style: Pan Head Diameter: Between 0.256 inches and 0.270 inches Head Height: Between 0.087 inches and 0.097 inches First Diameter From Head: Between 0.087 inches and 0.099 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Internal Drive Style: Slot Thread Diameter: 0.138 inches
Between 0.408 inches and 0.438 inches Head Style: Pan Head Diameter: Between 0.256 inches and 0.270 inches Head Height: Between 0.087 inches and 0.097 inches First Diameter From Head: Between 0.087 inches and 0.099 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Internal Drive Style: Slot Thread Diameter: 0.138 inches
Pan Head Diameter: Between 0.256 inches and 0.270 inches Head Height: Between 0.087 inches and 0.097 inches First Diameter From Head: Between 0.087 inches and 0.099 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Internal Drive Style: Slot Thread Diameter:
Pan Head Diameter: Between 0.256 inches and 0.270 inches Head Height: Between 0.087 inches and 0.097 inches First Diameter From Head: Between 0.087 inches and 0.099 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Internal Drive Style: Slot Thread Diameter:
Between 0.256 inches and 0.270 inches Head Height: Between 0.087 inches and 0.097 inches First Diameter From Head: Between 0.087 inches and 0.099 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Internal Drive Style: Slot Thread Diameter: 0.138 inches
Head Height: Between 0.087 inches and 0.097 inches First Diameter From Head: Between 0.087 inches and 0.099 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Internal Drive Style: Slot Thread Diameter: 0.138 inches
Between 0.087 inches and 0.097 inches First Diameter From Head: Between 0.087 inches and 0.099 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Internal Drive Style: Slot Thread Diameter: 0.138 inches
First Diameter From Head: Between 0.087 inches and 0.099 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Internal Drive Style: Slot Thread Diameter: 0.138 inches
Between 0.087 inches and 0.099 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Internal Drive Style: Slot Thread Diameter: 0.138 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Internal Drive Style: Slot Thread Diameter: 0.138 inches
Between 0.220 inches and 0.250 inches Internal Drive Style: Slot Thread Diameter: 0.138 inches
Internal Drive Style: Slot Thread Diameter: 0.138 inches
Slot Thread Diameter: 0.138 inches
Thread Diameter: 0.138 inches
0.138 inches
Thready Qty Per Inch (tpi):
32
Externally Relieved Body Diameter Quantity:
1
Material:
Steel comp 303
Material Specification:
Astm a582 cond a assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-f-14072, finish e300 military specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No

Externally Relieved Body Screw - Page 2 of 2



Fiig: A003b0

Mil-std (military Standard):

Mil-f-14072 spec.