NSN 5305-01-035-7638

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-035-7638 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.350 inches and 0.400 inches **Fastener Length:** Between 1.422 inches and 1.452 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.429 inches and 0.477 inches **Grip Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.081 inches first hole **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.312 inches **Grip Length:** Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** 100.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 0.113 inches first hole and 0.123 inches first hole Material: Steel **Material Specification:** 23-112, mcdonnel douglas corporation mfr ref single material response **Surface Treatment: Passivate Thread Series Designator:** Unjf Shelf Life: **Unit Of Measure:**

N/a **Demilitarization:** No

NSN 5305-01-035-7638

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0