NSN 5305-01-036-2673

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-036-2673 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.277 inches and 0.328 inches **Fastener Length:** Between 3.168 inches and 3.188 inches **Head Style:** Crowned hexagon **Head Height:** Between 0.126 inches and 0.141 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Grip Diameter:** Between 0.2487 inches and 0.2492 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.086 inches first hole **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches **Grip Length:** Between 2.750 inches and 2.766 inches Thready Qty Per Inch (tpi): 28 Distance From Head Largest Bearing Surface To Shank Hole Center: 3.073 inches first hole and 3.093 inches first hole Surface Finish: 32.0 microinches grip **Special Features:** Retaining element in shank Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:**

Unjf

NSN 5305-01-036-2673

Close Tolerance Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0