NSN 5305-01-037-2229

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-037-2229 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.110 inches **Fastener Length:** 0.245 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.134 inches and 0.140 inches **Head Height:** Between 0.083 inches and 0.086 inches **First Diameter From Head:** Between 0.084 inches and 0.086 inches **Second Diameter From Head:** Between 0.052 inches and 0.054 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.085 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.135 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 302 **Material Specification:** Qq-w-423, form i, condition b federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35, type 2 or 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-01-037-2229

Externally Relieved Body Screw - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A003b0