## NSN 5305-01-037-2411

**Thread Class:** 

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-037-2411

3a						
Thread Direction:						
Right-hand						
Thread Length:						
0.276 inches						
Fastener Length:						
Between 0.636 inches and 0.666 inches						
Head Style:						
Flat countersunk						
Head Diameter:						
Between 0.376 inches and 0.385 inches						
Grip Diameter:						
Between 0.1885 inches and 0.1895 inches						
Internal Drive Style:						
W/o internal drive						
Thread Diameter:						
0.190 inches						
Grip Length:						
Between 0.365 inches and 0.385 inches						
Thready Qty Per Inch (tpi):						
32						
Min. Tensile Strength (psi):						
160000 pounds per square inch						
Countersink Angle:						
100.0 degrees						
Surface Finish:						
32.0 microinches threads						
Material:						
Iron alloy 660						
Material Specification:						
Ams 5737 assn standard single material response						
Surface Treatment:						
Passivate						
Surface Treatment Specification:						
Qq-p-35 federal specification single treatment response						
Thread Series Designator:						
Unef						
Specification Data:						
80205-nas1153 professional/industrial association standard						
Shelf Life:						

N/a

## NSN 5305-01-037-2411

Close Tolerance Screw - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0