NSN 5305-01-037-6828

View Online at https://aerobasegroup.com/nsn/5305-01-037-6828

Shoulder Screw - Page 1 of 2

Thread Class:



За **Thread Direction:** Right-hand Thread Length: 0.360 inches **Fastener Length:** 1.410 inches **Head Style:** Flat chamfer **Head Diameter:** 0.440 inches **Head Height:** 0.220 inches **Shoulder Diameter:** 0.309 inches first shoulder and 0.311 inches first shoulder **Shoulder Length:** 0.747 inches first shoulder **Internal Drive Style:** Hexagon

Width Across Flats:

Thread Diameter:

0.250 inches

Between 0.156 inches and 0.158 inches

Thready Qty Per Inch (tpi):

28

Hardness Rating:

23.0 rockwell c and 32.0 rockwell c

Shoulder Shape:

Round first shoulder

Material:

Steel comp 1035 or steel comp 1536 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1541

Material Specification:

Astm a-546 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

NSN 5305-01-037-6828

Shoulder Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0