

View Online at <https://aerobasegroup.com/nsn/5305-01-037-8898>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.293 inches

Fastener Length:

Between 0.977 inches and 1.003 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.357 inches and 0.375 inches

Head Height:

Between 0.182 inches and 0.188 inches

Shoulder Diameter:

0.247 inches first shoulder and 0.248 inches first shoulder

Shoulder Length:

0.622 inches first shoulder and 0.628 inches first shoulder

Internal Drive Style:

Hexagon

Thread Diameter:

0.190 inches

Width Across Flats:

0.125 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 43.0 rockwell c

Shoulder Shape:

Round first shoulder

Special Features:

Pellet type locking element in threads

Material:

Steel

Surface Treatment:

Oxide

Surface Treatment Specification:

Ams 2485 assn standard single treatment response or mil-c-13924 military specification single treatment response

Thread Series Designator:

Unrc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.