

View Online at <https://aerobasegroup.com/nsn/5305-01-038-2566>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.328 inches

Fastener Length:

Between 0.468 inches and 0.500 inches

Head Style:

Pan

Head Diameter:

Between 0.357 inches and 0.373 inches

Head Height:

Between 0.122 inches and 0.132 inches

Washer Quantity:

2

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

55000 pounds per square inch

Secondary Washer Relationship To Primary Washer:

Not identical

Secondary Washer Style:

Flat

Primary Washer Outside Diameter:

0.334 inches

Secondary Washer Outside Diameter:

Between 0.338 inches and 0.348 inches

Primary Washer Style:

Split helical ring

Primary Washer Material Thickness:

0.047 inches

Secondary Washer Material Thickness:

Between 0.029 inches and 0.035 inches

Material:

Steel secondary washer

Material Specification:

Qq-s-698 federal specification 1st material response primary washer or mil-s-7952 military specification 2nd material response primary washer or mil-s-7952 military specification 3rd material response primary washer

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, cl 2 or 3 federal specification all treatment responses

Thread Series Designator:

Unc

Specification Data:

80205-nas 1301 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-7952 spec.