NSN 5305-01-038-2567

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-038-2567

View Online at https://aerobasegroup.com/nsn/5305-01-038-2567						
Thread Class:						
3a						
Thread Direction:						
Right-hand						
Thread Length:						
1.000 inches						
Fastener Length:						
Between 1.460 inches and 1.500 inches						
Head Style:						
Flat chamfer						
Head Diameter:						
Between 0.365 inches and 0.375 inches						
Head Height:						
Between 0.244 inches and 0.250 inches						
Internal Drive Style:						
Hexagon						
Thread Diameter:						
0.250 inches						
Width Across Flats:						
Between 0.188 inches and 0.190 inches						
Thready Qty Per Inch (tpi):						
28						
Min. Tensile Strength (psi):						
180000 pounds per square inch						
Hardness Rating:						
38.0 rockwell c and 45.0 rockwell c						
Minimum Yield Strength:						
150000 pounds per square inch						
Material:						
Steel uns k03104						
Material Specification:						
Astm a574 assn standard single material response						
Surface Treatment:						
Cadmium and chromate						
Surface Treatment Specification:						
Qq-p-416, type 2, class 2 federal specification single treatment response						
Thread Series Designator:						
Unrf						
Specification Data:						
80205-nas1351 professional/industrial association standard						
Shelf Life:						

N/a

NSN 5305-01-038-2567

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0