## NSN 5305-01-038-9530

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-038-9530 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.750 inches **Fastener Length:** Between 2.920 inches and 3.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.921 inches and 0.937 inches **Head Height:** Between 0.616 inches and 0.625 inches **Locking Feature:** Strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.625 inches Width Across Flats: Between 0.500 inches and 0.505 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel fastener **Surface Treatment:** Cadmium fastener and chromate fastener **Surface Treatment Specification:** Qq-p-416, type 2 class 2 federal specification single treatment response fastener **Thread Series Designator:** Unrc **Specification Data:** 80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

## NSN 5305-01-038-9530

Socket Head Cap Screw - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A003b0