## NSN 5305-01-039-2208

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-039-2208

Thread Direction: Right-hand Thread Length: Between 0.419 inches and 0.500 inches Fastener Length: Between 0.469 inches and 0.500 inches Head Style: Fillister Head Diameter: Between 0.166 inches and 0.183 inches Head Height: Between 0.072 inches and 0.079 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Screw Material: Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 303se Screw Material Specification: Aisi assn standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Thread Class:
Thread Direction: Right-hand Thread Length: Between 0.419 inches and 0.500 inches Fastener Length: Between 0.469 inches and 0.500 inches Head Style: Fillister Head Diameter: Between 0.166 inches and 0.183 inches Head Height: Between 0.072 inches and 0.079 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Screw Material: Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 303se Screw Material Specification: Aisi assn standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Right-hand Thread Length: Between 0.419 inches and 0.500 inches Fastener Length: Between 0.469 inches and 0.500 inches Head Style: Fillister Head Diameter: Between 0.166 inches and 0.183 inches Head Height: Between 0.072 inches and 0.079 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Screw Material: Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 303se Screw Material Specification: Aisi assn standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Thread Length: Between 0.419 inches and 0.500 inches Fastener Length: Between 0.469 inches and 0.500 inches Head Style: Fillister Head Diameter: Between 0.166 inches and 0.183 inches Head Height: Between 0.072 inches and 0.079 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Screw Material: Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 303se Screw Material Specification: Aisi assn standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Between 0.419 inches and 0.500 inches  Fastener Length: Between 0.469 inches and 0.500 inches  Head Style: Fillister  Head Diameter: Between 0.166 inches and 0.183 inches  Head Height: Between 0.072 inches and 0.079 inches Internal Drive Style: Cross recess type 1  Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40  Screw Material: Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 303se  Screw Material Specification: Aisi assn standard all material responses  Screw Surface Treatment: Passivate  Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response  Thread Series Designator: Unc Shelf Life: N/a  Unit Of Measure: Demilitarization: No	
Fastener Length: Between 0.469 inches and 0.500 inches Head Style: Fillister Head Diameter: Between 0.166 inches and 0.183 inches Head Height: Between 0.072 inches and 0.079 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Screw Material: Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 303se Screw Material Specification: Aisi assn standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	-
Between 0.469 inches and 0.500 inches  Head Style: Fillister  Head Diameter: Between 0.166 inches and 0.183 inches  Head Height: Between 0.072 inches and 0.079 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Screw Material: Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 303se Screw Material Specification: Aisi assn standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Head Style: Fillister Head Diameter: Between 0.166 inches and 0.183 inches Head Height: Between 0.072 inches and 0.079 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Screw Material: Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 303se Screw Material Specification: Aisi assn standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	-
Fillister  Head Diameter: Between 0.166 inches and 0.183 inches  Head Height: Between 0.072 inches and 0.079 inches  Internal Drive Style: Cross recess type 1  Thread Diameter: 0.112 inches  Thready Qty Per Inch (tpi): 40  Screw Material: Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 303se  Screw Material Specification: Aisi assn standard all material responses  Screw Surface Treatment: Passivate  Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response  Thread Series Designator: Unc  Shelf Life: N/a  Unit Of Measure: Demilitarization: No	
Head Diameter: Between 0.166 inches and 0.183 inches Head Height: Between 0.072 inches and 0.079 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Screw Material: Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 303se Screw Material Specification: Aisi assn standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	•
Between 0.166 inches and 0.183 inches  Head Height: Between 0.072 inches and 0.079 inches  Internal Drive Style: Cross recess type 1  Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40  Screw Material: Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 303se Screw Material Specification: Aisi assn standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Fillister
Head Height: Between 0.072 inches and 0.079 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Screw Material: Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 303se Screw Material Specification: Aisi assn standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Head Diameter:
Between 0.072 inches and 0.079 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Screw Material: Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 303se Screw Material Specification: Aisi assn standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Between 0.166 inches and 0.183 inches
Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Screw Material: Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 303se Screw Material Specification: Aisi assn standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Head Height:
Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Screw Material: Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 303se Screw Material Specification: Aisi assn standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Between 0.072 inches and 0.079 inches
Thread Diameter:  0.112 inches Thready Qty Per Inch (tpi): 40 Screw Material: Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 303se Screw Material Specification: Aisi assn standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Internal Drive Style:
O.112 inches Thready Qty Per Inch (tpi): 40 Screw Material: Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 303se Screw Material Specification: Aisi assn standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Cross recess type 1
Thready Qty Per Inch (tpi):  40  Screw Material: Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 303se  Screw Material Specification: Aisi assn standard all material responses  Screw Surface Treatment: Passivate  Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response  Thread Series Designator: Unc  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No	Thread Diameter:
Screw Material: Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 303se Screw Material Specification: Aisi assn standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.112 inches
Screw Material:  Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 303se  Screw Material Specification:  Aisi assn standard all material responses  Screw Surface Treatment:  Passivate  Screw Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:  Unc  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Thready Qty Per Inch (tpi):
Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 303se  Screw Material Specification: Aisi assn standard all material responses  Screw Surface Treatment: Passivate  Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response  Thread Series Designator: Unc  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No	40
Screw Material Specification: Aisi assn standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Screw Material:
Aisi assn standard all material responses  Screw Surface Treatment:  Passivate  Screw Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:  Unc  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 303se
Screw Surface Treatment:  Passivate  Screw Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:  Unc  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Screw Material Specification:
Passivate  Screw Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:  Unc  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Aisi assn standard all material responses
Screw Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:  Unc  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Screw Surface Treatment:
Qq-p-35 federal specification single treatment response  Thread Series Designator: Unc  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No	Passivate
Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Screw Surface Treatment Specification:
Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Qq-p-35 federal specification single treatment response
Shelf Life: N/a Unit Of Measure: Demilitarization: No	Thread Series Designator:
N/a Unit Of Measure: Demilitarization: No	Unc
Unit Of Measure: Demilitarization: No	Shelf Life:
Demilitarization:	N/a
No	Unit Of Measure:
No	
	Demilitarization:
	No
Filg:	Fiig:
A500d0	-