NSN 5305-01-040-1612

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-040-1612 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.438 inches **Fastener Length:** 2.094 inches **Head Style:** Pan no. 2 **Head Diameter:** 0.314 inches **Head Height:** 0.110 inches **Internal Drive Style:** Cross recess type ii **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch **Hardness Rating:** Between 26.0 rockwell c and 32.0 rockwell c **Product Name:** Navy special project **Screw Material:** Steel comp 8630 or steel comp 4037 **Screw Material Specification:** Mil-s-6050 military specification 1st material response or mil-s-8695 military specification 2nd material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type 2 class 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5305-01-040-1612

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.