NSN 5305-01-041-9629

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-041-9629

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.320 inches and 0.370 inches |
| Fastener Length: |
| Between 0.768 inches and 0.798 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.337 inches and 0.383 inches |
| Grip Diameter: |
| Between 0.1885 inches and 0.1895 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.428 inches and 0.448 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5737 assn standard single material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 2 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 81205-bacs12lh professional/industrial association standard |
| Shelf Life: |
| N/a |

Unit Of Measure:

NSN 5305-01-041-9629

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0