## NSN 5305-01-042-4425

Thumbscrew - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5305-01-042-4425



TI	hread Class:
2a	a
TI	hread Direction:
Ri	ight-hand
TI	hread Length:
B	etween 0.790 inches and 0.910 inches
Fa	astener Length:
B	etween 1.220 inches and 1.280 inches
H	ead Style:
Kı	nurled no. 1
H	ead Diameter:
B	etween 0.280 inches and 0.340 inches
H	ead Height:
B	etween 0.470 inches and 0.530 inches
Fi	irst Diameter From Head:
B	etween 0.080 inches and 0.085 inches
D	istance From Largest Bearing Surface Of Head To End Of First Diameter:
B	etween 0.370 inches and 0.430 inches
P	oint Style:
FI	at
TI	hread Diameter:
0.	112 inches
Т	hready Qty Per Inch (tpi):
4(	)
E	xternally Relieved Body Diameter Quantity:
1	
P	roduct Name:
N	avy special project
Μ	aterial:
St	teel comp 4130
Т	hread Series Designator:
U	nc
S	helf Life:
N	/a
U	nit Of Measure:
D	emilitarization:
N	0
Fi	iig:
A	003b0