## NSN 5305-01-042-6318

**Thread Class:** 

За

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-042-6318

Thread Direction:
Right-hand
Thread Length:
Between 0.410 inches and 0.457 inches
Fastener Length:
Between 0.598 inches and 0.645 inches
Head Style:
Pan
Head Diameter:
Between 0.473 inches and 0.492 inches
Head Height:
Between 0.162 inches and 0.175 inches
Hole Diameter:
0.037 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.250 inches
Grip Length:
0.188 inches
Hole Quantity:
2
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Round longitudinal hole
Surface Finish:
63.0 microinches grip
Product Name:
Navy special project
Special Features:
Dry film lubricant
Material:
Titanium alloy uns r54520

## NSN 5305-01-042-6318

Close Tolerance Screw - Page 2 of 2



Thread Series Designator:	
Unjf	
Specification Data:	
26512-gb511j professional/industrial association standard	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

INO

Fiig:

A003b0