## NSN 5305-01-042-7546

Shoulder Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-042-7546

| 2a<br>Thread Direction:<br>Right-hand<br>Thread Length:<br>0.150 inches<br>Fastener Length:<br>0.320 inches<br>Head Style:<br>Flat countersunk<br>Head Diameter:<br>Between 0.245 inches and 0.250 inches<br>Shoulder Diameter:<br>0.182 inches first shoulder and 0.186 inches first shoulder<br>Shoulder Length:<br>0.105 inches first shoulder<br>Internal Drive Style:<br>Torque |
|--|
| Right-hand<br>Thread Length:<br>0.150 inches<br>Fastener Length:<br>0.320 inches<br>Head Style:<br>Flat countersunk<br>Head Diameter:<br>Between 0.245 inches and 0.250 inches<br>Shoulder Diameter:<br>0.182 inches first shoulder and 0.186 inches first shoulder<br>Shoulder Length:<br>0.105 inches first shoulder<br>Internal Drive Style:<br>Torque                            |
| Thread Length:<br>0.150 inches<br>Fastener Length:<br>0.320 inches<br>Head Style:<br>Flat countersunk<br>Head Diameter:<br>Between 0.245 inches and 0.250 inches<br>Shoulder Diameter:<br>0.182 inches first shoulder and 0.186 inches first shoulder<br>Shoulder Length:<br>0.105 inches first shoulder<br>Internal Drive Style:<br>Torque  |
| 0.150 inches<br>Fastener Length:<br>0.320 inches<br>Head Style:<br>Flat countersunk<br>Head Diameter:<br>Between 0.245 inches and 0.250 inches<br>Shoulder Diameter:<br>0.182 inches first shoulder and 0.186 inches first shoulder<br>Shoulder Length:<br>0.105 inches first shoulder<br>Internal Drive Style:<br>Torque  |
| Fastener Length:0.320 inchesHead Style:Flat countersunkHead Diameter:Between 0.245 inches and 0.250 inchesShoulder Diameter:0.182 inches first shoulder and 0.186 inches first shoulderShoulder Length:0.105 inches first shoulderInternal Drive Style:Torque  |
| 0.320 inches<br>Head Style:<br>Flat countersunk<br>Head Diameter:<br>Between 0.245 inches and 0.250 inches<br>Shoulder Diameter:<br>0.182 inches first shoulder and 0.186 inches first shoulder<br>Shoulder Length:<br>0.105 inches first shoulder<br>Internal Drive Style:<br>Torque  |
| Head Style:<br>Flat countersunk<br>Head Diameter:<br>Between 0.245 inches and 0.250 inches<br>Shoulder Diameter:<br>0.182 inches first shoulder and 0.186 inches first shoulder<br>Shoulder Length:<br>0.105 inches first shoulder<br>Internal Drive Style:<br>Torque  |
| Flat countersunk<br>Head Diameter:<br>Between 0.245 inches and 0.250 inches<br>Shoulder Diameter:<br>0.182 inches first shoulder and 0.186 inches first shoulder<br>Shoulder Length:<br>0.105 inches first shoulder<br>Internal Drive Style:<br>Torque   |
| Head Diameter:<br>Between 0.245 inches and 0.250 inches<br>Shoulder Diameter:<br>0.182 inches first shoulder and 0.186 inches first shoulder<br>Shoulder Length:<br>0.105 inches first shoulder<br>Internal Drive Style:<br>Torque   |
| Between 0.245 inches and 0.250 inches<br>Shoulder Diameter:<br>0.182 inches first shoulder and 0.186 inches first shoulder<br>Shoulder Length:<br>0.105 inches first shoulder<br>Internal Drive Style:<br>Torque   |
| Shoulder Diameter:<br>0.182 inches first shoulder and 0.186 inches first shoulder<br>Shoulder Length:<br>0.105 inches first shoulder<br>Internal Drive Style:<br>Torque  |
| 0.182 inches first shoulder and 0.186 inches first shoulder<br><b>Shoulder Length:</b><br>0.105 inches first shoulder<br><b>Internal Drive Style:</b><br>Torque  |
| Shoulder Length:<br>0.105 inches first shoulder<br>Internal Drive Style:<br>Torque   |
| 0.105 inches first shoulder<br>Internal Drive Style:<br>Torque   |
| Internal Drive Style:<br>Torque  |
| Torque   |
|  |
| There al Discussion  |
| Thread Diameter:   |
| 0.112 inches   |
| Thready Qty Per Inch (tpi):  |
| 40   |
| Min. Tensile Strength (psi):   |
| 180000 pounds per square inch  |
| Countersink Angle:   |
| 90.0 degrees   |
| Shoulder Shape:  |
| Round first shoulder   |
| Material:  |
| Stainless steel  |
| Thread Series Designator:  |
| Unc  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A003b0   |
|  |