NSN 5305-01-043-1369

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-043-1369 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.308 inches and 0.375 inches **Fastener Length:** Between 0.943 inches and 0.990 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.325 inches and 0.385 inches **Grip Diameter:** Between 0.1885 inches and 0.1894 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.615 inches and 0.635 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 220000 pounds per square inch **Hardness Rating:** 28.0 rockwell c and 50.0 rockwell c **Countersink Angle:** 100.0 degrees **Surface Finish:** 32.0 microinches grip **Product Name:** Navy special project Material: Steel comp h11 **Surface Treatment:** Cadmium **Thread Series Designator:** Unjf **Specification Data:** 26512-gb510b professional/industrial association standard Shelf Life:

N/a

NSN 5305-01-043-1369

Close Tolerance Screw - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A003b0