

View Online at <https://aerobasegroup.com/nsn/5305-01-043-1370>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.306 inches and 0.357 inches

Fastener Length:

Between 2.290 inches and 2.310 inches

Head Style:

Crowned hexagon

Head Height:

Between 0.157 inches and 0.172 inches

Width Between Flats:

Between 0.492 inches and 0.502 inches

Grip Diameter:

Between 0.3112 inches and 0.3117 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Internal Drive Style:

Slot

Thread Diameter:

0.312 inches

Grip Length:

Between 1.812 inches and 1.828 inches

Thready Qty Per Inch (tpi):

24

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.177 inches first hole and 2.197 inches first hole

Surface Finish:

32.0 microinches threads

Special Features:

Retaining element in shank

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0