
## NSN 5305-01-043-1373

Close Tolerance Screw - Page 1 of 2

3a





## **Thread Class: Thread Direction: Right-hand Thread Length:** Between 0.306 inches and 0.357 inches Fastener Length: Between 2.540 inches and 2.560 inches **Head Style:** Crowned hexagon **Head Height:** Between 0.157 inches and 0.172 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Grip Diameter:** Between 0.3112 inches and 0.3117 inches Shank Unthreaded Hole Diameter: 0.076 inches first hole and 0.086 inches first hole **Internal Drive Style:** Slot **Thread Diameter:** 0.312 inches Grip Length: Between 2.062 inches and 2.078 inches Thready Qty Per Inch (tpi): Distance From Head Largest Bearing Surface To Shank Hole Center: 2.427 inches first hole and 2.447 inches first hole Surface Finish: 32.0 microinches grip **Special Features:** Retaining element in shank Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment:** Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response

## **Thread Series Designator:**

Unjf

24

## NSN 5305-01-043-1373

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

