## NSN 5305-01-043-1879

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-043-1879

View Online at https://aerobasegroup.com/nsn/5305-01-043-1879
Thread Class:
3
Thread Direction:
Right-hand
Thread Length:
Between 0.211 inches and 0.278 inches
Fastener Length:
Between 0.908 inches and 0.955 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.325 inches and 0.385 inches
Grip Diameter:
Between 0.1885 inches and 0.1894 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.190 inches
Grip Length:
Between 0.677 inches and 0.697 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Countersink Angle:
100.0 degrees
Surface Finish:
32.0 microinches grip
Product Name:
Navy special project
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Cadmium or cadmium and chromate
Surface Treatment Specification:
Nas 672 assn standard 1st treatment response or mil-c-8837 type 2 cl 2 military specification 2nd treatment response
Thread Series Designator:

Unjf

## NSN 5305-01-043-1879

Close Tolerance Screw - Page 2 of 2



Sı	ne	cif	icat	ion	Data:
٧ı	٧٠	···	ıcaı		Data.

26512-gb510n manufacturers standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.