NSN 5305-01-043-1884

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-043-1884

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.755 inches and 0.822 inches
Fastener Length:
Between 3.703 inches and 3.750 inches
Head Style:
Flat countersunk
Head Diameter:
Between 1.007 inches and 1.017 inches
Grip Diameter:
Between 0.4982 inches and 0.4991 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.500 inches
Grip Length:
Between 2.928 inches and 2.948 inches
Thready Qty Per Inch (tpi):
20
20
20 Min. Tensile Strength (psi):
20 Min. Tensile Strength (psi): 160000 pounds per square inch
20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating:
20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle:
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish:
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches grip
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches grip Material:
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment:
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification:
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator:
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf

N/a

NSN 5305-01-043-1884

Close Tolerance Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0