## NSN 5305-01-043-4301

Close Tolerance Screw - Page 1 of 2





## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.349 inches and 0.416 inches Fastener Length: Between 0.984 inches and 1.031 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.469 inches and 0.474 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches Grip Length: Between 0.615 inches and 0.635 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** 100.0 degrees Surface Finish: 63.0 microinches threads **Product Name:** Navy special project Material: Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 or steel comp 4130 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, class 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 26512-gb510l manufacturers standard Shelf Life:

N/a

## NSN 5305-01-043-4301

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

