NSN 5305-01-043-5736

Close Tolerance Screw - Page 1 of 2



Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.266 inches and 0.334 inches
Fastener Length:
Between 1.714 inches and 1.761 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.447 inches and 0.507 inches
Grip Diameter:
Between 0.2483 inches and 0.2492 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.250 inches
Grip Length:
Between 1.428 inches and 1.448 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Countersink Angle:
100.0 degrees
Surface Finish:
32.0 microinches grip
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 1 cl 3 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:

26512-gb510n professional/industrial association standard

NSN 5305-01-043-5736

Close Tolerance Screw - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0