
## NSN 5305-01-043-5736

Close Tolerance Screw - Page 1 of 2





**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.266 inches and 0.334 inches Fastener Length: Between 1.714 inches and 1.761 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.447 inches and 0.507 inches **Grip Diameter:** Between 0.2483 inches and 0.2492 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches Grip Length: Between 1.428 inches and 1.448 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c **Countersink Angle:** 100.0 degrees Surface Finish: 32.0 microinches grip Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response Surface Treatment: Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 1 cl 3 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 

26512-gb510n professional/industrial association standard

## NSN 5305-01-043-5736

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

