NSN 5305-01-043-5750

Close Tolerance Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-043-5750



or steel comp 8740 or steel comp 4130

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.365 inches and 0.432 inches
Fastener Length:
Between 1.250 inches and 1.297 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.555 inches and 0.560 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.375 inches
Grip Length:
Between 0.865 inches and 0.885 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
100.0 degrees
Surface Finish:
63.0 microinches threads
Product Name:
Navy special project
Material:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
200540 sh 540l avefaceional (inductrial accessibility standard

26512-gb510l professional/industrial association standard

NSN 5305-01-043-5750

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

