## NSN 5305-01-043-5752

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-043-5752

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.365 inches and 0.432 inches
Fastener Length:
Between 1.563 inches and 1.610 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.555 inches and 0.560 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.375 inches
Grip Length:
Between 1.178 inches and 1.198 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
100.0 degrees
Surface Finish:
63.0 microinches threads
Product Name:
Navy special project
Mark to the
Material:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 or steel comp 4130
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 or steel comp 4130
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 or steel comp 4130 <b>Surface Treatment:</b>
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 or steel comp 4130  Surface Treatment:  Cadmium and chromate
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 or steel comp 4130  Surface Treatment:  Cadmium and chromate  Surface Treatment Specification:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 or steel comp 4130  Surface Treatment:  Cadmium and chromate  Surface Treatment Specification:  Qq-p-416, type 2, class 2 federal specification single treatment response

26512-gb510l professional/industrial association standard

## NSN 5305-01-043-5752

Close Tolerance Screw - Page 2 of 2



She	lf I	Life	е:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0