## NSN 5305-01-043-7702

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-043-7702



## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.219 inches and 0.312 inches Fastener Length: Between 0.281 inches and 0.312 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.265 inches and 0.270 inches **Head Height:** Between 0.088 inches and 0.102 inches Hole Diameter: 0.047 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.164 inches **Hole Quantity:** Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response Head Hole Configuration Style: Round **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1101 professional/industrial association standard Shelf Life: N/a

2

## NSN 5305-01-043-7702

Machine Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A500d0

