
Close Tolerance Screw - Page 1 of 2





Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.171 inches and 0.221 inches
Fastener Length:
Between 0.361 inches and 0.391 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.258 inches and 0.305 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.190 inches
Grip Length:
Between 0.170 inches and 0.190 inches
Thready Qty Per Inch (tpi):
32
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
100.0 degrees
Surface Finish:
63.0 microinches grip
Product Name:
Navy special project
Material:
Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 3 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-01-043-7719

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

