

View Online at <https://aerobasegroup.com/nsn/5305-01-043-8868>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.250 inches and 0.317 inches

Fastener Length:

Between 0.885 inches and 0.932 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.297 inches and 0.302 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Internal Drive Style:

High-torque

End Application:

Aircraft, phantom f-4; aircraft, eagle f-15; aircraft, f-16

Thread Diameter:

0.190 inches

Grip Length:

Between 0.615 inches and 0.635 inches

Thread Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Countersink Angle:

100.0 degrees

Surface Finish:

63.0 microinches grip

Material:

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 or steel comp 4130

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

26512-gb510l professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0