## NSN 5305-01-043-9644

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-043-9644 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.202 inches **Fastener Length:** 0.375 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** Between 0.090 inches and 0.095 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.170 inches and 0.175 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Product Name:** Navy special project Material: Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 **Material Specification:** Qq-s-763 federal specification all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Gss7021, fscm 26512 mfr ref single treatment response **Thread Series Designator:** Unc

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5305-01-043-9644

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0