

View Online at <https://aerobasegroup.com/nsn/5305-01-044-2239>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.750 inches and 1.000 inches

Fastener Length:

Between 0.969 inches and 1.000 inches

Head Style:

Hexagon

Head Height:

Between 0.150 inches and 0.163 inches

Width Between Flats:

Between 0.428 inches and 0.438 inches

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

52000 pounds per square inch

Material:

Copper alloy 462 or copper alloy 464 or copper alloy 482 or copper alloy 482 or copper alloy 485 or copper alloy 230 or copper alloy 240 or copper alloy 260 or copper alloy 268 or copper alloy 342 or copper alloy 353 or copper alloy 360 or copper alloy 377 or copper alloy 764 or copper alloy 270 or copper alloy 510 or copper alloy 745 or copper alloy 752 or copper alloy 770

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0