NSN 5305-01-044-2246

Close Tolerance Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-044-2246

Thread Class: 3a Thread Direction: Right-hand Thread Length: Between 0.504 inches and 0.571 inches Fastener Length: Between 0.592 inches and 0.599 inches Head Style: Flat countersunk undercut Head Diameter: Between 0.629 inches and 0.633 inches Head Piejht: Between 0.381 inches and 0.090 inches Grip Diameter: Between 0.381 inches and 0.120 inches Head Height: Between 0.3115 inches and 0.120 inches Internal Drive Style: High-torque Thread Diameter: 0.312 inches Grip Length: Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads
Thread Direction:Right-handThread Length:Between 0.504 inches and 0.571 inchesFastener Length:Between 0.952 inches and 0.999 inchesHead Style:Flat countersunk undercutHead Diameter:Between 0.629 inches and 0.633 inchesHead Height:Between 0.088 inches and 0.1900 inchesGrip Diameter:Between 0.3115 inches and 0.3120 inchesInternal Drive Style:High-torqueThread Diameter:0.312 inchesOrip Length:Between 0.428 inches and 0.448 inchesThread Diameter:0.312 inchesGrip Length:Between 0.428 inches and 0.448 inchesThready Oty Per Inch (tpi):24Countersink Angle:100.0 degreesSurface Finish:32.0 microinches threads
Right-hand Thread Length: Between 0.504 inches and 0.571 inches Fastener Length: Between 0.952 inches and 0.999 inches Head Style: Flat countersunk undercut Head Diameter: Between 0.629 inches and 0.633 inches Head Height: Between 0.088 inches and 0.633 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Internal Drive Style: High-torque Thread Diameter: 0.312 inches Grip Length: 10.312 inches Grip Length: 21 chread Diameter: 0.312 inches Grip Length: 10.428 inches and 0.448 inches Thread Diameter: 10.0 degrees 24 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads
Thread Length: Between 0.504 inches and 0.571 inches Fastener Length: Between 0.952 inches and 0.999 inches Head Style: Flat countersunk undercut Head Diameter: Between 0.629 inches and 0.633 inches Head Height: Between 0.088 inches and 0.090 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Internal Drive Style: High-torque Thread Diameter: 0.312 inches 0.312 inches Grip Length: Between 0.428 inches and 0.448 inches Thready Dy Per Inch (tpi): 24 Countersink Angle: 10.0.0 degrees Surface Finish: 32.0 microinches threads
Between 0.504 inches and 0.571 inchesFastener Length:Between 0.952 inches and 0.999 inchesHead Style:Flat countersunk undercutHead Diameter:Between 0.629 inches and 0.633 inchesHead Height:Between 0.088 inches and 0.090 inchesGrip Diameter:Between 0.088 inches and 0.3120 inchesInternal Drive Style:High-torqueThread Diameter:0.312 inchesGrip Lameter:Between 0.428 inches and 0.448 inchesThread Diameter:0.312 inchesGrip Length:Between 0.428 inches and 0.448 inchesThready Qty Per Inch (tpi):24Countersink Angle:100.0 degreesSurface Finish:20.0 microinches threads
Fastener Length:Between 0.952 inches and 0.999 inchesHead Style:Flat countersunk undercutHead Diameter:Between 0.629 inches and 0.633 inchesHead Height:Between 0.088 inches and 0.090 inchesGrip Diameter:Between 0.3115 inches and 0.3120 inchesInternal Drive Style:High-torqueThread Diameter:0.312 inchesBetween 0.428 inches and 0.448 inchesThread Diameter:0.312 inchesGrip Length:Between 0.428 inches and 0.448 inchesThready Qty Per Inch (tpi):24Countersink Angle:100.0 degreesSurface Finish:32.0 microinches threads
Between 0.952 inches and 0.999 inchesHead Style:Flat countersunk undercutHead Diameter:Between 0.629 inches and 0.633 inchesHead Height:Between 0.088 inches and 0.090 inchesGrip Diameter:Between 0.3115 inches and 0.3120 inchesInternal Drive Style:High-torqueThread Diameter:0.312 inchesGrip Length:Between 0.428 inches and 0.448 inchesThready Qty Per Inch (tpi):24Countersink Angle:100.0 degreesSurface Finish:32.0 microinches threads
Head Style:Flat countersunk undercutHead Diameter:Between 0.629 inches and 0.633 inchesHead Height:Between 0.088 inches and 0.090 inchesGrip Diameter:Between 0.3115 inches and 0.3120 inchesInternal Drive Style:High-torqueThread Diameter:0.312 inchesGrip Length:Between 0.428 inches and 0.448 inchesThready Qty Per Inch (tpi):24Countersink Angle:100.0 degreesSurface Finish:32.0 microinches threads
Flat countersunk undercutHead Diameter:Between 0.629 inches and 0.633 inchesHead Height:Between 0.088 inches and 0.090 inchesGrip Diameter:Between 0.3115 inches and 0.3120 inchesInternal Drive Style:High-torqueThread Diameter:0.312 inchesGrip Length:Between 0.428 inches and 0.448 inchesThready Qty Per Inch (tpi):24Countersink Angle:100.0 degreesSurface Finish:32.0 microinches threads
Head Diameter:Between 0.629 inches and 0.633 inchesHead Height:Between 0.088 inches and 0.090 inchesGrip Diameter:Between 0.3115 inches and 0.3120 inchesInternal Drive Style:High-torqueThread Diameter:0.312 inchesGrip Length:Between 0.428 inches and 0.448 inchesThready Uty Per Inch (tpi):24Countersink Angle:100.0 degreesSurface Finish:32.0 microinches threads
Between 0.629 inches and 0.633 inchesHead Height:Between 0.088 inches and 0.090 inchesGrip Diameter:Between 0.3115 inches and 0.3120 inchesInternal Drive Style:High-torqueGrip Length:Between 0.428 inches and 0.448 inchesThready Qty Per Inch (tpi):24Countersink Angle:100.0 degreesSurface Finish:32.0 microinches threads
Head Height:Between 0.088 inches and 0.090 inchesGrip Diameter:Between 0.3115 inches and 0.3120 inchesInternal Drive Style:High-torqueThread Diameter:0.312 inchesGrip Length:Between 0.428 inches and 0.448 inchesThready Qty Per Inch (tpi):24Countersink Angle:100.0 degreesSurface Finish:32.0 microinches threads
Between 0.088 inches and 0.090 inchesGrip Diameter:Between 0.3115 inches and 0.3120 inchesInternal Drive Style:High-torqueThread Diameter:0.312 inchesGrip Length:Between 0.428 inches and 0.448 inchesThready Qty Per Inch (tpi):24Countersink Angle:100.0 degreesSurface Finish:32.0 microinches threads
Grip Diameter:Between 0.3115 inches and 0.3120 inchesInternal Drive Style:High-torqueThread Diameter:0.312 inchesGrip Length:Between 0.428 inches and 0.448 inchesThready Qty Per Inch (tpi):24Countersink Angle:100.0 degreesSurface Finish:32.0 microinches threads
Between 0.3115 inches and 0.3120 inchesInternal Drive Style:High-torqueThread Diameter:0.312 inchesGrip Length:Between 0.428 inches and 0.448 inchesThready Qty Per Inch (tpi):24Countersink Angle:100.0 degreesSurface Finish:32.0 microinches threads
Internal Drive Style:High-torqueThread Diameter:0.312 inchesGrip Length:Between 0.428 inches and 0.448 inchesThready Qty Per Inch (tpi):24Countersink Angle:100.0 degreesSurface Finish:32.0 microinches threads
High-torqueThread Diameter:0.312 inchesGrip Length:Between 0.428 inches and 0.448 inchesThready Qty Per Inch (tpi):24Countersink Angle:100.0 degreesSurface Finish:32.0 microinches threads
Thread Diameter:0.312 inchesGrip Length:Between 0.428 inches and 0.448 inchesThready Qty Per Inch (tpi):24Countersink Angle:100.0 degreesSurface Finish:32.0 microinches threads
Grip Length: Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads
Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads
Thready Qty Per Inch (tpi): 24 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads
24 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads
Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads
100.0 degrees Surface Finish: 32.0 microinches threads
Surface Finish: 32.0 microinches threads
32.0 microinches threads
Matarial
Material:
Steel
Surface Treatment:
Passivate
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: A003b0